

## PRODUCT SPEC SHEET CAP-24LED3-L

## 24" BNC FRAMELESS **LED MONITOR**

24/7/365 Operating Capability



The 24" BNC frameless LED monitor is designed to excel in 24/7 video surveillance applications. Delivering full HD resolution and 16.7 million colors, the monitor displays every detail with precision. HDMI and VGA inputs and a BNC input/output easily accommodate multiple devices and allow for BNC looping. The monitor also features source auto detection and quick touch scalability for quick setup.

## **FEATURES**

- 23.8" Diagonal Viewing Size
- 1920x1080P Full HD Resolution
- 178° Ultra-Wide Viewing Angle
- Source Auto Detection
- Low Blue Light Technology
- Quick Touch Scalability 16:9/4:3
- BNC, VGA, HDMI and Audio Inputs
- Includes VGA, Audio and Dual Power Cables (EU,UK)
- Two Built-In Speakers
- 36-Month Warranty

**SELECT SERIES** 

- Part #: CAP-24LED3-L
- UPC: 840049312241
- Length: 21.3" (541mm)
- Width: 8.6" (218.4mm)
- Height: 15.8" (401.3mm)
- Weight: 5.95 lbs. (2.69kg)
- UL Listed









## PRODUCT SPEC SHEET CAP-24LED3-L

ADI	
TECHNICAL SPECIFICATIONS	
Model	CAP-24LED3-L
Screen Diagonal Dimension (inches)	23.8"
Viewable Area W x H	20.7" x 11.6" (525.7mm x 294.6mm)
LED Type	Edge LED
Pixel Pitch (mm)	0.2745mm x 0.2745mm
Screen Maximum Resolution	1920x1080
Display Resolutions	720x400; 640x480; 800x600; 1024x768; 1280x1024; 1366x768; 1920x1080
Supported Input Resolutions	720x400; 640x480; 800x600; 1024x768; 1280x1024; 1366x768; 1920x1080
Refresh Rate (hertz)	60Hz
Color Depth (millions)	16.7 million colors
Brightness	250 nits (250 cd/m²)
Auto Adjust	Yes
Monitor Aspect Ratio	16:9
Display Aspect Ratio	OSD options: Full/4:3/Over Scan
Horizontal TV Lines	1080
Contrast Ratio	4000:1SCR
Response Time (ms)	5 ms (GTG)
View Angle H/V (degrees)	178° x 178°/CR>10
Digital Video Inputs	HDMI up to 1920x1080
Analog Video In/Out	VGA up to 1920x1080
Connectors	HDMI x 1, VGA x 1, BNC IN x 1, BNC OUT x 1, AUDIO OUT x 1
Audio Inputs (stereo)	1 x 3.5mm mini-jack
Speakers (watts)	2 x 2 watts
Stand-by (watts)	<0.5 watt
Power Consumption (watts)	19 watts typical
Monitor Body Dimensions	21.3" x 1.6" x 12.6" (541mm x 40.6mm x 312.4mm)
Dimensions Monitor+Stand	21.3" x 8.6" x 15.8" (541mm x 218.4mm x 401.3mm)
Panel Surface	Matte black
Case and Stand Material	Plastic
VESA Mounting Pattern (mm)	100mm x 100mm
Base/Stand Included	Yes
Base Tilt Angle	-5°~15°
Weight Cabinet Only	5.18 lbs. (2.34kg)
Weight Cabinet+Base Stand	5.95 lbs. (2.69kg)
Power Supply (internal)	AC 100-240V~50/60Hz 1.1A
Operating Temperature	0°C~40°C / 32°F~104°F
Storage Temperature	-20°C~50°C / -4°F~122°F
Operating Humidity	10-90%
Accessories Included in the Box	Dual power cable(EU,UK)/VGA cable/Audio cable/IR Remote Stand support/Screws/Base of stand/User manuals
Mounting Screw Size (mm)	M4-L8 mm/4pcs
Certifications	CE/FCC/RoHS/HDMI/UL/WEEE/REACH/UKCA
Warranty	36 Months
	1 55