
SPEC SHEET



FULL HD PRO-GRADE LED COLOUR MONITOR

WBXML32



This professional grade widescreen LED 31.5" colour monitor offers HDMI, VGA, & BNC inputs. With an additional BNC looping output its versatility will allow it to work for any application. Boasting 16.7 million colours & FHD Resolution this monitor will make your video come to life.

- 31.5" Diagonal Viewing Size
- 1920x1080P Full HD Resolution
- VGA, BNC & HDMI Inputs
- 24/7 Operation
- IPS Technology, 178° Viewing Angle
- Source Auto Detection
- Quick Touch Scalability 16:9/4:3
- Includes Audio, VGA & Dual Power Cables (EU,UK)
- 36 Month Warranty

PART #: WBXML32

UPC: 811914029878

LENGTH:

28.8inch/731.4mm WIDTH:

6.3inch/160mm HEIGHT:

19.6inch/497.5mm

WEIGHT: 27.9lbs/12.7kg



SPEC SHEET



Model	WBXML32
	31.5
Viewable Area WxH (inches/mm)	27.5inch*15.47inch / 698.5mm*393mm
Led Type	LED
Pixel Pitch (mm)	0.36x0.36
Screen Maximum Resolution	1920x1080
Display Resolutions	640 x 480; 800 x 600; 1024 x 768; 1280 x 1024; 1920 x 1080
Supported Input Resolutions	640 x 480; 800 x 600; 1024 x 768; 1280 x 1024; 1920 x 1080
• • • • • • • • • • • • • • • • • • • •	
Refresh Rate (Hz)	60
Color Depth (M)	16.7
Brightness (cd/m²)	300
Auto Adjust	Yes
Monitor Aspect Ratio	16:9
Display Aspect Ratio	OSD selectable 16:9 or 4:3
Horizontal TV Lines	1080
Contrast Ratio	3000 :1SCR
Response Time (ms)	5 (GTG)
View Angle H/V (degrees)	178°x 178°/CR>10
Digital Video Inputs	HDMI up to 1920 x1080
Analog Video In/Out	VGA up to 1920x1080, BNC CVBS looping
Audio Inputs (stereo)	1x3.5mm mini-jack
Speakers (W)	2 x 5
Stand-by (W)	< 0.5
Power Consumption	50W Typical
Monitor Body Dimensions (inches/mm)	28.8inchx17inchx1.9inch / 731.4mmx432.5mmx49mm
Dimensions Monitor+Stand (inches/mm)	28.8inchx19.6inchx6.3inch / 731.4mmx497.5mmx160mm
Panel Surface	Matte black
Case & Stand Material	Metal + Aluminum (removable stand)
VESA Mounting Pattern (mm)	200 x 200
Base/Stand Included	Yes
Base Tilt Angle	-5°~15°
Weight Cabinet Only (lb/kg)	21.1lbs / 9.6kg
Weight Cabinet+Base Stand (lb/kg)	22.9lbs / 10.4kg
Power Supply (internal)	AC 100-240V~50/60Hz 1.1A
Operating Temperature	0°C~40°C / 32°F~104°F
Storage Temperature	-20°C~50°C / -4°F~122°F
Operating Humidity	10~90%
Accessories	Dual Power cable (EU,UK)/VGA cable/Audio cable/IR Remote/Batteries Allen wrench/Screws/Base of stand/Stand support/User manuals
Rack Mount Screw Size (mm)	Screws for Mounting Monitor, Screws Type: HMФ6.0x10mm/4pcs Screws for Securing Base of Stand, Screws Type: KMФ4.0x10mm/6pcs Screws for Installing Monitor Stand, Screws Type: HMФ6.0x10mm/4pcs
Certifications	CE/FCC/ROHS/HDMI/UL/WEEE/REACH
Warranty	36 Months