



HikCentral 1.5


Make the surveillance much easier.

Co je HikCentral?

HikCentral je SW platforma pro centrální řešení a správu nejen kamerového systému. Nabízí širokou škálu aplikací pro malé, střední a velké instalace, a k tomu disponuje přehledným rozhraním pro koncové uživatele.




HikCentral



Hikvision Management Server

Co je HikCentral?

HikCentral is Enterprise Level integrated security management software. It features strong integrated security solutions for different vertical application scenarios and easy management for end-users.



Management

- CCTV
- Access Control & Attendance
- Facial Recognition
- ANPR Management
- UVSS(Under Vehicle Surveillance System)
- People counting & Heat map
- Smart Video Wall
- Event & Alarm Management
- User and Role Permission Control
- E-MAP & GIS Map
- RSM(remote site management)
- Open SDK


Základní vlastnosti

Management


- Zařízení & Logické celky [sites]
- Správa záznamu video & audio dat
- Správa alarmových událostí [HW, SW, ...]
- Správa uživatelů [AD]
- E-MAP
- Systémová konfigurace

Uživatelské rozhraní

- Práce s živým obrazem & záznamem
- Inteligentní vyhledávání
- Správa exportu video&audio dat
- Správa alarmových událostí
- Log stavu systému
- E-MAP
- Podpora tepelných map , počítání osob , ANPR



Struktura systému



• Server Layer

- ✓ SYS Server
- ✓ ADS Server
- ✓ Streaming Server

• Client Layer

- ✓ Web Client
- ✓ Control Client/Mobile/Pad Client

• Device Layer


- ✓ Cameras, NVR/DVR Access
- ✓ pStor/Hybrid SAN/Cloud Storage Server/**Face Recognition Server**
- ✓ Decoder/Video Wall Controller/Keyboard
- ✓ Door Controller/**Face Recognition Terminal**/Hikvision Turnstile
- ✓ Security Control Panel/Alarm Station/**Alarm Hub**
- ✓ Under-Vehicle Surveillance System
- ✓ **Dock Station**

Architecture

Small to Medium

One HikCentral VSM Server


- Manage up to 3,000 cameras



Medium to Large

Two HikCentral Server (Distributed)


- Manage up to 10,000 cameras




Super Large

N+1 HikCentral Server_(RSM)

- Manage up to 100,000 cameras



1.3 Server Central/Distributed Management



SYS	Resource Management
	Device Access
	Base Applications
	System Database
	System Management
	System Services
ADS	Event & Alarm
	Face / ANPR / BI / Card / ...
	Runtime Database
	Other Applications

Kompletní „All In One“ řešení



Přeinstalovaný Software*

Přeinstalovaný HikCentral na prověřeném a kompatibilním HW zařízení, **Hikvision management server** řeší problémy s hardwarovou nekompatibilitou.

Před-aktivovaná Licence*

Hikvision management server je dodáván s aktivovanou licencí na 64/300 kanálů pro urychlení instalace a nastavení.

Instalace systému během pár minut

„Lightweight“ instalační modul redukuje čas instalace na minimum.

** Hikvision management server je doporučeno používat pouze jako server. Doporučujeme dodat PC s klientem.*

Efektivní živý náhled a přehrávání

HikCentral Control Client je profesionální řešení určené k trvalému dohledu, disponuje vysokou stabilitou a nabízí mnoho uživatelských funkcí.

Vysoká efektivita pro koncové uživatele

- Až 3 doplňkové obrazovky pro více kanálů, živý náhled, podpora až pro 256 kamer v živém náhledu.
- Až 8 doplňkových obrazovek pro multi-task operace




Uživatelské rozhraní



Mobile Client

Živý obraz & záznam &
události & PTZ




PC Control Client & Video Wall

- Klientská PC stanice s podporou více monitorů
- Možnost správy videostěny [dekodéry a 3D klávesnice]





Web Client

Tenký PC klient



2.1 Monitoring

■ Smooth stream for low bandwidth solution





Notes: Auto-change the bitrates between clients and NVR/IPC according to the network capacity without manual triggering.

NEW

Visual tracking

Tracking |

Associate several cameras/ Pops up automatically.



- Associated cameras to improve monitoring efficiency

- Exporting an integrated video footage from multiple cameras, which contains the whole process of the target person's movement
- Avoiding wasting time clicking irrelevant video footage

Přehledná správa alarmů

Upozornění na poplachovou situaci

- Notifikace o poplachových stavech se zobrazují okamžitě v živém zobrazení a ve stromové struktuře.
- Intuitivní správa alarmů v „Poplachovém okně“, seznam alarmů, videa a lokalizace alarmu v mapě.
- Identifikace, rozpoznání a odbavení poplachu



Report alarmů a událostí

Support creating Event /Alarm Report on Control Client

- Support generate report by multiple condition in Event & Alarm Search
- Support PDF , Excel , CSV formatting export

Event Report				
Basic Information				
3	Search Time:	2018/02/06 18:10:53		
4	Search by:	admin		
5	Triggering Event:	User-Defined Event		
6	Time:	2018/02/06 00:00:00 - 2018/02/06 23:59:59		
7	Total Number:	5000		
Name	Alarm Source Type	Triggering Event	Time	
10 12345rr	12345rr	User-Defined Event	2018/2/6 18:07	
11 23ttt	23ttt	User-Defined Event	2018/2/6 18:07	




- Alarm list support **Area** information displaying
- Each alarm in alarm list could jump to **Alarm Search** and automatically fill in the alarm source , event type and more (e.g. LPR events come with plate number, vehicle list)

Podpora reportů - Web Client

- Podpora PDF a Excel format
- Podpora email reportu - Den/Týden
- Až 32 alarmů/ událostí může být reportováno v rámci jednoho reportu
- Až 10,000 alarmů/ událostí celkem

Podpora mapových podkladů a správa alarmových událostí

- Mapové podklady
- Správa alarmových událostí
- Správa alarmových vstupů & výstupů
- Monitorování živého obrazu & záznamu
- Integrace se smart video wall




Monitoring



Map Management

Google GIS Map / E-Map help operators to know the location of resource;




Locate the site of the event or alarm through Google GIS Map / E-Map

Efektivní přehrávání záznamu

Nezávislé přehrávání záznamu a živého zobrazení


- Umožnuje simultáně přehrávat záznam z kamery a zároveň v druhém zobrazení sledovat živý náhled.



2.1.5 Efficient Video Playback

Visualized Operations on the Timeline

- Quick Event Positioning with Thumbnail*
- From double-click camera to start playback: 1 second
- Rapidly acquire video clips around the target time and get all the following videos by simply dragging your timeline.



*CVR: DS-A81016S, DS-A82012d, DS-A82024d, DS-A81024D, DS-A80624S. FW: V2.3.4

IPC with only SD storage: not supported.

If the CVR was in LAN, Client is in WAN, it only support. when CVR has been done the port mapping. .

2.1.5 Efficient Video Investigation

Video Search

- Multiple ways to search video: by tag, by locked status, by interval, by time, by file, etc.
- Thumbnails are supported for quicker positioning*;
- Quick playback with List mode is supported for all storage types.


CVR: DS-A81016S, DS-A82024d, DS-A81024D, DS-A80624S. FW: V2.3.4

NVR: DS-76xxNI-I, DS-77xxNI-I, DS-96xxNI-I, DS-96xxxNI-I. FW: N/A

DVR: TVI 4.0 F series. FW: N/A

IPC with only SD storage: not supported.

If the CVR was in LAN, Client is in WAN, it only support when CVR has been done the port mapping.



2.1.5 Efficient Video Search

“After-the-fact” VCA Search * of playback video available for convenient analysis.

- Motion Analysis
- Line Crossing Detection
- Intrusion Detection
- **CVR VCA Search**



CVR: DS-A81016S, DS-A82024d, DS-A81024D, DS-A80624S. FW: V2.3.2-5.

NVR: DS-96xxNI-ST/I, DS-86xxNI-ST/I, DS-86xxNI-RT/I, DS-96xxNI-RT/I,

DS-86xxNI-XT/I, DS-96xxNI-XT/I. FW: V3.2.0 Build150211.

DVR: TVI 3.0 F series. FW: V3.4.0 build151201


IPC: DS-2CD2T22WD-I3, DS-2CD2320-I, DS-2CD4A25FWD-IZS, etc. FW: V5.3.0_150211

If the CVR was in LAN, Client is in WAN, it only support. when CVR has been done the port mapping. . .

2.1 Monitoring




- Add tag information for post-event search



Video Tagging




- Protect the video from cyclic rewriting



Overwrite protection



- Encrypt and export the video files



Encryption & Exportation

Ochrana soukromí osob

- Rozpixelování osob
- Dynamické nebo statické rozpixelování
- Ochrana soukromí na základě přístupových práv do systému

Rozpixelování živého zobrazení i záznamu

- Možnost definování rozpixelování osob při exportu záznamu
- Podpora na straně NVR pro až 4 kanály
- Integrace do jednotného SW HikCentral



DS-2CD7126G0-IZS



+

DS-9632NXI-I8/8F (B)



+

HikCentral




Recording Management



Multi-Storage Media

Various storage resource choice



Evidence Management

Evidence management for organized the video, Unified the operation

The screenshot displays a user interface for managing video evidence. On the left, a grid of 32 recorded video entries is shown, each corresponding to a camera and timestamp. On the right, a specific incident is detailed, showing surveillance footage from three cameras at an 'east gate accident' scene. The interface allows for filtering and navigating through the recorded evidence.

pStor: Hikvision pStor is a lightweight Windows-based Video and Picture storage software

Recording Management



Video Search / Video Export


A screenshot of a dark-themed dashboard titled "My Dashboard". It features several sections: "Surveillance" (Monitoring, Alarm Center), "Investigation" (Alarm & Event Search, Video Search, Vehicle Search, Access Control), "Video Analysis" (People Analysis, Heat Map, Temperature, Vehicle Analysis), "Maintenance" (Health Monitoring, Audit Trail), "Tool" (Smart Wall, VSPlayer, Broadcast, Alarm Output Control, Two-Way Audio), and "Management" (Download Center, Local Picture, Local Recording, System, Help). The "Video Search" option under "Investigation" is highlighted.

Search the recording after event / alarm




Recording Backup

Real time backup & scheduled backup from local storage to central storage



- **Daytime:** Normal business data flow occupies the network bandwidth, so recording files are stored on local sites.
- **Nighttime:** Network resources released for video central backup.

Pokročilá správa uživatelských práv




- Centrální správa a nastavení uživatelských práv: správce systému může spravovat celý systém a přiřadit různá oprávnění různým operátorům, umožnit více uživatelům přihlásit se současně prostřednictvím rozdílných klientů
- „Bezešvá“ integrace se službou Active Directory pro správu uživatelských práv

Pokročilá správa uživatelských práv


HIKVISION

Role



Každý uživatel může mít přiřazeno více rolí.

Uživatel



HikCentral sjednocená platforma

Kamerový systém

- Výkonný a efektivní
- Centralizovaná správa

Instalace

- Kontrola přístupu
- Video stěna
- ANPR
- POS vyhledávání
- Počítání lidí
- Heat Map


Otevřená platforma

- Podpora Onvif
- Otevřená SDK podpora

Sjednocená platforma

HikCentral je sjednocená platforma, která zahrnuje kamerové systémy, kontrolu přístupu, ANPR, POS a systémy třetích stran.

Podpora integrace do systému třetích stran



**Podporované
moduly a
aplikace**



Contents


Part 2.2

Dock Station Management

2.2 Dock Station Management

With Hikvision Dock Station and Body Camera, video evidence can be easily managed on HikCentral.

- Search video evidence across multiple Dock Stations by person
- Upload video evidence to SFTP server from different Clients
- Search evidence quickly by predefined marks



Smart Wall



Basic Function

- Live View and Playback on smart wall
- Window split and restore/Roaming window operation/Window stitching/Display Stream details in the Control Client / Operators' right management



General operation based on video wall



Advanced Function

- Alarm Pop-up and recovery
- Auto-display alarm-related camera or view



Operators' right management

2.3 Smart Wall (Graphic Card)




Image Operation

- Live view on screen
- Display view/view group
- Display face comparison/ access control/ANPR events in live view
- Auto display of alarm-related video
- Display GIS map/E-map on screen
- Display health monitoring page on screen

2.3 Smart Wall (Keyboard)



DS-1200KI (V1.1.0)
smart wall (decoding device)



DS-1100KI (V 3.1 or V4.0)
smart wall (decoding device)



DS-1600KI (V 3.1.0)
smart wall (decoding device)



DS-1005KI (V1.3.1)
smart wall (graphic card)



Upgraded

Access Control



Basic Access Control Management

- Flexible authorized time / access point
- Flexible authorized personnel
- Multiple access credentials (including temporary cards)



Card



Password



Video Access
Control Terminal



Fingerprint



Advanced Access Control Applications

- Anti-passback / multi-door interlocking rule
- Extended access / super permission
- First card remain unlocked / first card authorization
- One button open or close all doors
- Entry & exit counting rule

The screenshot displays a software interface for managing access control and video surveillance. On the left, a sidebar shows a tree view of system components: HikCentral-V1.3 B2, ACCESS CONTROLLER 1, Facial Rec Terminal, and Super NVR. A red box highlights the 'Call Center Door 01' entry under ACCESS CONTROLLER 1. The main area consists of two video feeds showing a hallway. Red lines on the floor indicate a walkway. A callout box in the top right of the video feeds identifies the person as 'Phil Wring' and notes 'Access Granted' at '17:36:10'. Below the video feeds is a timeline with event details: 'Access Granted by Card' at 'Showroom Door 01_Cardreade...' on '12/09/18 17:36:10'. At the bottom, there are buttons for 'All Events', 'Face Comparison', 'Access Control', and 'Subscribe All', along with a table for viewing event logs.

Video Surveillance & Access Control Linkage
for high-level security area



Elevator Control

Integrated with Hikvision Elevator Control, HikCentral supports managing elevator system to improve your building solution.



Quickly configure the relationship between people and floors



The elevator can be manually controlled in the control client, and quickly deactivated in an emergency.



More than 50 events & alarms, real-time client reception and quick video review



Able to adjust visitor's access range

NEW

Visitor Management

Registration

The front-desk clerks visitors, uploads photos, IDs and some key information



Visitors Coming

Visitors come to the front desk

Permission Assignment

Assign visitors access rights and credentials (support cards, fingerprints, faces and QR codes)

Records Trace

Bidding farewell to paper records, historical visitor records are saved in the system and can be searched quickly.



Upgraded

Time and Attendance



Basic Attendance Management


- Core time period attendance
- Allow late arrival and early departure
- Support weekend setting, absence setting
- Overtime setting, leave type configuration



Fingerprint Terminal




Face Recognition Terminal




Advanced Attendance Management

- Manage attendance record (search attendance record, correct attendance record)
- Configure attendance report
- Third-party integration
- Non-sensing attendance



Security Control

Integrated with Hikvision security control device, HikCentral supports managing alarm system to enhance security.



Education

A collage of images illustrating security control components and their applications. The top row shows: a white rectangular security radar unit, a white security control panel with a keypad and antenna, a black circular axiom hub, and a blue panic alarm station with a red button and a camera on a pole. The bottom row shows: a retail store interior with shelves of shoes, a modern office building lobby with large windows, and a person using an ATM machine.

Retail

Building

ATM

Smart

Deep-learning Technology

Smart



ANPR systém / detekce SPZ vozidel

The screenshot shows the Blazer Express ANPR software interface. On the left, there's a search panel with fields for Camera (All), Country, Plate Number, Owner, and Time, along with a Filter button. Below it is a table of tracked vehicles:

Plate Number	Time	Camera	Owner	Telephone	Country
TR.MS917	2014/11/12 19:05:05	Camera 01	John Wang	486214586	America
TR.MS917	2014/11/12 19:05:05	Camera 01	John Wang	486214586	America

The main area displays a live video feed of a dark-colored car with the license plate "TR MS917". Below the video are sections for "Owner Information" (Owner: John Wang, Telephone: 486214586) and "Vehicle Information" (Vehicle Passing Time: 2014/11/12 19:05:05, Country: America). At the bottom, there's a "Device Information" section (Camera Name: Camera 01) and a pagination control.

ANPR živé zobrazení

- ◆ Podpora živého zobrazení ANPR
- ◆ Manuální přepínání živého zobrazení & fotografie vozu
- ◆ Zobrazení 1/2/4/9/16





Vehicle Management



HikCentral provides entrance & exit management with ANPR Camera and UVSS.



- License plate recognition (set effective period for vehicle list)
- Real-time vehicle whitelist/blacklist alarm
- History vehicle information search(central site & remote site)
- Export vehicle analysis report



- Auto detection of vehicle undercarriage
- Synchronize LPR camera data with under vehicle picture
- Comparison with original undercarriage picture
- Mark suspicious area
- Vehicle list alarm



ANPR: Automatic Number Plate Recognition





UVSS: Under Vehicle Scanning system



Upgraded

Business Intelligence

BI dashboard provides a **flexible, customized** tabular view interface to inform decision makers with business analysis reports.



Business Intelligence

Intelligent Analysis can optimize store layout, advise promotion time, and even provide commercial tendency for decision-makers.

① People Counting




- Multi-channel cameras displaying
- Up to 200+ cameras data export per site
- Support export of remote sites data
- Email report



② Heat Analysis




- Check the line chart of Dwell Time or People Amount
- People amount/Dwell time comparison of heat map cameras



③ People Feature Analysis



- shows the proportion of persons with different features
- refers to the gender and age group




NEW

Business Intelligence

Queue Analysis


- Accurate counting result of human number
- Waiting time of each person and total person number per queue
- Export exception numbers, person in queue and queue status report



Route Analysis



- Analyze people amount on the pathways in shopping malls or stores
- Move the cursor to camera icon to check line chart/heat map of people amount and people dwell time



Temperature Analysis



- Display temperature exception numbers of different presets
- Display temperature data of single thermometry point
- Check the max/min temperature



POS - integrace – pokladní systémy

The screenshot displays a POS system interface with several windows:

- Top Bar:** POS Live, Business Intelligent, POS Search.
- Left Panel:** Receipt Number, Tagged Footage, Event. It shows a list of transactions with columns: Date, Time, Store, Terminal, Cashier, and Receipt No.
- Middle Panel:** A detailed receipt for "SAVAROVSKI" from "Swarovski Boutique NETHERLANDS 1012 PA AMSTERDAM". The receipt includes details like address, phone number, and ticket number (Ticket 46356). Below it is a transaction table with items like "PURITY ARMBAND RHS" and "BURLEY HANGER".
- Bottom Panel:** A "Playback" window showing a video frame of a cashier at a counter. A green box highlights the transaction data overlaid on the video, with the text "Video Frame & Transaction Data (Synchronized)". A yellow arrow points from the text box to the video frame.




Analýza transakčních dat

- ✓ Transakční reporty
- ✓ Objem prodejů komodit
- ✓ Nejprodávanější položky
- ✓ Kontrola na úrovni pokladna/ video záznam



Face Recognition

HikCentral is equipped with powerful face capture and comparison functions with the intelligent devices provided by Hikvision, including DeepinView, DeepinMind and Face Recognition Server.



Display face capture/comparison in real time



Search by captured pictures/matched pictures/frequently appeared persons' pictures





Support alarm notification triggered by face match/mismatch or frequently appeared faces



Support face Comparison Group Management

Detekce obličeje

Detekce obličeje, vyhledávání a filtrace výsledků v rámci záznamu



Face Recognition Access Control

Facial Recognition Access Control makes it more convenient and efficient.



- ✓ Use person faces as credentials
- ✓ Support single faces and all the combined authentication modes
- ✓ Use facial recognition terminals as attendance points

NEW

Non-sensing Attendance



HikCentral Professional Web Client

> Attendance Settings Shift Schedule Records and Handling > Attendance Report Third-Party Database

Export | Calculate Again | Get from Device | Set Regular Report | Batch Handle | Handling Records

Time Period: Daily | Time: Last 7 Days | Attendance Group: All | Filter | Reset

Person Name: [] Status: All

Name	ID	Date	Attend...	Status	Schedule...	Requir...	Actual Work Time	Late	Early L...	Break	Leave	OT1	OT2	OT3	Total OT
Sherry ...	35041...	2019-10-...	Support...	Normal	0930-1800	8h	10:10-19:55(8h 44min)	0h	0h	1h	0h	0h	0h	0h	0h
Sherry ...	35041...	2019-10-...	Support...	Normal	0930-1800	8h	10:10-19:55(8h 44min)	0h	0h	1h	0h	0h	0h	0h	0h
Hunter ...	425052...	2019-10-...	Support...	Absent	0800-1800	9h	--19:55(0h)	0h	0h	1h	0h	0h	0h	0h	0h
Hunter ...	425052...	2019-10-...	Support...	Normal	0930-1800	8h	10:10-19:55(8h 44min)	0h	0h	1h	0h	0h	0h	0h	0h
Tian Xu	445617...	2019-10-...	Support...	Normal	0930-1800	8h	10:10-19:55(8h 44min)	0h	0h	1h	0h	0h	0h	0h	0h
Tian Xu	445617...	2019-10-...	Support...	Normal	0930-1800	8h	10:10-19:55(8h 44min)	0h	0h	1h	0h	0h	0h	0h	0h
Nicole ...	574137...	2019-10-...	presales	Absent	0800-1800	9h(0h)	0h	0h	0h	0h	0h	0h	0h	0h
Nicole ...	574137...	2019-10-...	Support...	Normal	0930-1800	8h	10:10-19:55(8h 44min)	0h	0h	1h	0h	0h	0h	0h	0h
Forrest ...	603606...	2019-10-...	Support...	Normal	0930-1800	8h	10:10-19:55(8h 44min)	0h	0h	1h	0h	0h	0h	0h	0h
Forrest ...	603606...	2019-10-...	presales	Absent	0800-1800	9h(0h)	0h	0h	0h	0h	0h	0h	0h	0h
wilam C...	611590...	2019-10-...	Support...	Normal	0930-1800	8h	10:10-19:55(8h 44min)	0h	0h	1h	0h	0h	0h	0h	0h
wilam C...	611590...	2019-10-...	Support...	Normal	0930-1800	8h	10:10-19:55(8h 44min)	0h	0h	1h	0h	0h	0h	0h	0h



- ✓ Non-sensing attendance by face recognition
- ✓ Supports face recognition in cameras or in intelligent fusion servers



Security

Cyber Security

Cybersecurity


Video and stream encryption double safeguard your data




User
Exports a video
to local disk



Lawbreaker
steals the video
from the user



- **Description:** While saving video to local disk, user can conduct encryption to the file. Password is needed when opening the file.
- **Application Scenario:** For some key and confidential evidence, user can encrypt it. So even the file was stolen, it cannot be played.



NVR/DVR conducts AES encryption in the stream to protect the video, which requires password to play the video. So the transmission from NVR/DVR to the platform is better secured.



- **Risk:** If the stream is illegally got by someone, video will be leaked.
- **Solution:** Conduct AES encryption to the video, thus even when the stream is leaked, video data will still be unavailable.

Note: HikCentral Professional can also support Https encryption and system login authentication for higher security.




Maintenance

Health Monitoring, History
Overview, Audit Trail, Error
Diagnosis, Key Data Backup and
Batch Devices Upgrading

Maintenance


Health Monitoring

Check the status of devices and system




Audit Trail

Search the error/warning/information



History Overview

Overview the history status of devices and system



NEW

Error Diagnosis

Show errors details and guide you how to solve it



The screenshot shows the 'Monitoring' tab in the HikCentral Professional Control Client. A red alert box highlights a 'Zero Camera' device with the error code '00-0000-0000'. The 'Diagnosis Details' panel provides information about the device, its connection status, exception descriptions, and suggestions for troubleshooting.

This dialog box allows users to backup system data. It includes a 'Type' section with checkboxes for various data types like Configured Data, Configured Pictures, Received Events, etc. Below are dropdown menus for 'How Often' (Monthly), 'Which Day' (1), and 'When' (0:00). At the bottom are 'Save', 'Save and Back Up Now', and 'Cancel' buttons.

Batch Upgrading

Upgrade multiple devices' firmware simultaneously and schedule supported




Key Data Backup

Back up and restore system data

This dialog box offers two upgrade methods: 'Via Current Web Client' and 'Via EZVIZ Cloud'. It includes options for 'Upgrade by' (SYS Server or Local PC), 'Simultaneous Upgrade' (set to 5), and 'Upload Package from Local PC'. A 'Next' button is visible at the bottom right.


2.6 Health Monitoring

- Overall running status of the system
- New GUI with adaptive panel display
- Display system status, such as CPU, RAM, Network Speed and Streaming usage
- Refresh the resource status immediately or set the auto-refresh value



2.6 Error Diagnose

- More detailed error message
- Mark the error message and leave suggestion for reference to other operators
- Quickly jump to Event/Server/Device log and Health Monitoring interface



Diagnosis

Device Information

Name: Camera 01
IP: 10.6.6.251
Area Name: NVR

Exception Description

Live View Failed.No permission{Error Code: Control Client, HCNetSDK.dll [2]}

Suggestion

Please contact the administrator or our technical support.

Requesting URL completed.
Getting stream from Encoding Device failed.


Name: NVR
Address: 10.6.6.251
Online: Online
Channel Status: Online
Connections: 0

[Event Log](#) [Server Log](#) [Device Logs](#) [Health Mon...](#)

Mark


please call 12345

2.6 Batch Upgrade Firmware



Multi-Devices

Supports upgrade multiple devices' firmware, such as IPC, NVR, DVR, Access controller, Alarm Station etc...



Multi-Ways

Supports local and Ezviz upgrade. Support server and remote client upgrade.



Multi-Channels

Supports upgrading 5 channels simultaneously



Multi-Schedules

Supports multiple upgrading schedules with progress feedback and operation button

Service



Free SSP

Software Support Plan



Free SUP

Software Upgrading
Program



Customization

Personalized Requirement
Development

Note: For the free period of SSP/SUP and the fee of customization, please contact local Hikvision team.

Děkuji!